

RKT-1200



Basic Router Features

- Industrial robust design and compact metal housing
- High data speed via 4G LTE
- Strong electromagnetic interference Resistance, heat endurance and radiation ability
- Supports multiple VPN (PPTP, L2TP, GPE, IPSec etc.)
- Supports multiple network protocol (ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS etc.)
- Supports multiple functions (DHCP, DNS, DDNS, Firewall, NAT, DMZ host etc.)
- Built-in watch dog, Multi-link detection ensures working in stable and secure way
- Network failover and failback
- 2xLAN or 1xLAN + 1xWAN
- WAN port support PPPoE, static IP, DHCP client, 3G/4G.
- Always online, automatic reboot if disconnected to ensure continual connection
- LCP/ICMP/flow/heartbeat check, to ensure network usability
- Web/CLI/SSH/Management platform support, easy to configure
- SNMP network management, NTP support
- Local & remote management (configuration, status, upgrade firmware, ping, reboot)
- Supports Port forwarding and Bridge
- Supports timing operation
- Supports LED status indication
- Shock and vibration resistant
- Control by SMS, Email
- Schedule reboot

Advance Router Features

Too long to list

Specifications

RKT-1200

Module:	Telit LE910-SV1
Carrier Approvals:	Verizon
Regulatory Approvals:	FCC/IC, PTCRB, GCF
Frequency Bands:	B2(1900), B4(AWS1700), B13(700)
Data Speeds LTE:	DL 10 Mbps/ UL 5 Mbps

Router

VPN:	IPSec, PPTP/L2TP Client, GRE, PPTP Server
Protocol:	ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS etc.
Management:	Local or remote web browser (IE v8 or above), CLI/Telnet command, Remote management, SSH configure
Interface Type:	2 x 10/100 Mbps LAN port(RJ45) LED: "WLAN", "WAN", "LAN", "NET" 2 x SMA-K antenna interface SIM/UIM: 1.8V/3V Power: "PWR" 5V ~ 30V Reset: "RST"
Power Adapter:	Certificate: FCC, UL
Power Consumption:	Idle: <45mA@12VDC Data: <300mA@12VDC Average:150mA@12VDC
Physical:	Operating Temperature Storage: -40°C to 85°C Working: -30°C to 75°C Humidity: 95% Maximum (Non-condensing)
Dimensions:	Item (L x W x H): 4 x 2.9 x 1 Inch Packaging (L x W x H): 8.6 x 4.7 x 3 Inch Weight Item: 1 lbs. Packaging: 2.1 lbs. total weight including product
Certificate:	FCC, ISO, CE, RoHS
Package Content:	WTI 2 Port Router CAT5 Ethernet Cable Power Adapter 2 x Cellular Antenna - Mag Mount