

SiriUs

The New ATM Standard for Today and Tomorrow

SiriUs is built based on, with highest reliability standard, ease of operation, and most cost effective maintenance all in the smallest package possible for the most versatile placement.



Compact Design

SiriUs with its unique compact design, has the smallest footprint in its class. Measuring only at 14" x 22"x47" (W*D*H), making it extremely versatile, being able to fit virtually anywhere.

Reliability

With proven high quality parts and even details like metal function keys and pinpads, and specially designed cabinet, SiriUs will give you the maximum uptime.

Operation and Maintenance

Due to its unique cassette and dispenser design, being the smallest and lightest and having the least moving parts, result in most durable with lowest error rate and most economical replacement.

Tomorrow Standard

With EMV and PCI 3.0 standard, you can be sure to rely on the machine for the years to come.

Versatility

SiriUs has the widest range of cassette options in its class. Even offering two 1K cassettes for most effective dispensing to three 2K cassettes for the most volume. You can be sure to find the perfect balance of option for you.

Complete Package With Ultimate Versatility



High Topper attachable (option)

Display

- 8" color TFT LCD with 2X4 metal function keys
- Resolution(800 X 600)
- Touch (Option)

Card reader

- Dip Card Reader (EMV Level 1, 2)

Printer

- Thermal printer
- Sheet size: 3" (80mm)

System Platform / CPU

- Operating system : Windows CE 6.0
- Embedded, ARM11 533/667Hz
- Electronic journal

ADA

- Voice Guidance (Earphone Jack)
- Braille Keypad

Language

- English, Spanish, and Korean

Communication

- TCP/IP (SSL/TLS) or Dial up

Dispenser

- 1,000 note removable cassette (LCDM) : 1K
- Two 1,000 note removable cassettes (LCDM) : 2K
- 2,000 note removable cassette (ECDM) : 2K
- Two 2,000 note removable cassettes (ECDM) : 4K
- Three 2,000 note removable cassettes (ECDM) : 6K

Keypad

- 4X4 numeric metal keypad
- PCI EPP 3.0
- Triple DES EPP
- ADA Compliant

Operation Environment

- Power : AC 110/220V, 50/60Hz, 200W
- Operation temperature :
32 °F ~ 104 °F (0°C ~ 40°C)

Security

- UL291 Business Hour
- Electronic Lock

Dimensions / Weight

- Width 14" (356mm)
- Depth 22" (565mm)
- Height 47" (1200mm)
- Weight 165lb (75Kg)



PULOON Technology Inc.

