

SiriUs II

The New ATM Standard for Today and Tomorrow

SiriUs II is our latest model targeted for high-end ATM market with advanced functionalities and Puloon's market proven dispensers. It guarantees reliable & high-level performance and offers competitive pricings for our retail customers.

Quality Design

SiriUs II provides looks with durability, stability and reliability perfectly suited for financial industry. Yet its classy and attractive design draws attention especially with 15" large screen.

Additional Features

Additional features for the SiriUs II include earphone jack for voice guidance, EPP indicator, illuminated topper embedded in top area, and optional bar code reader.

Operation and Maintenance

Most parts in SiriUs II are compatible with its predecessor (SiriUs I) which are already proven in the market. This provides advantages to customers for easy maintenance and operation.

Standard Compliance

With EMV and PCI 3.0 standard along With UL291 business hour safe with electronic lock, you can rely on our SiriUs II for the years to come.

Versatility

With SiriUs II, you can choose from multiple 1K, 2K, 4K, 6K, and 8K cassette options for maximum volume. We can help you decide on the best option



Complete Package With Ultimate Versatility

SiriUs II Specification



Display

- 15" color TFT LCD with 2x4 function keys
- Resolution(1024 x 768)
- Touch (Option)

Card reader

- Dip Card Reader (EMV Level 1, 2)

Printer

- Thermal printer
- Sheet size: 3" (80mm)

System Platform / CPU

- Operating system : Windows CE 6.0
- Embedded, ARM11 533/667Hz
- Electronic journal

ADA

- Voice Guidance (Earphone Jack)
- Braille Keypad

Language

- English, Spanish, and Korean

Communication

- TCP/IP (SSL/TLS) or Dial up

Dispenser

- 1,000 note removable cassette (LCDM) :1K
- Two 1,000 note removable cassettes (LCDM) :2K
- 2,000 note removable cassette (ECDM) :2K
- Two 2,000 note removable cassettes (ECDM) :4K
- Three 2,000 note removable cassettes (ECDM) :6K
- Four 2,000 note removable cassettes (ECDM) :8K

Keypad

- 4X4 numeric metal keypad
- PCI EPP 3.0
- Triple DES EPP
- ADA Compliant

Operation Environment

- Power : AC 110/220V, 50/60Hz, 200W
- Operation temperature : 32 °F ~ 104 °F (0 °C ~ 40 °C)

Security

- UL291 Business Hour
- Electronic Lock

Dimensions / Weight

- Width 18.1" (460mm)
- Depth 23.6" (600mm)
- Height 56.3" (1430mm)
- Weight 220.5lb (100Kg)



PULCOON Technology Inc.

