



6500 Series Routers



Basic Router Features

- Industrial robust design and compact metal housing
- High data speed via 4G LTE, 3G and 2G backward compatible
- Strong electromagnetic interference resistance, heat endurance and radiation ability
- Supports multiple VPN (IPSec, OpenVPN, VPN Client, GRE etc.)
- Supports multiple network protocol (ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS etc.)
- Supports multiple functions (DHCP, DNS, DDNS, Firewall, NAT, DMZ host etc.)
- Built-in watch dog, Multi-link detection ensures working in stable and secure way
- Network failover and failback
- Bandwidth Control
- 5xLAN or 4xLAN + 1xWAN
- WAN port support PPPoE, static IP, DHCP client, 4G/3G.
- Always online, automatic reboot if disconnected to ensure continual connection
- LCP/ICMP/flow/heartbeat check, to ensure network usability
- Web/CLI/SSH/Management platform support, easy to configure
- SNMP network management, NTP support
- Local & remote management (configuration, status, upgrade firmware, ping, reboot)
- Supports Port forwarding and Bridge
- Supports timing operation
- Supports LED status indication
- Shock and vibration resistant
- Control by SMS, Email
- Schedule reboot

Advance Router Features

Too long to list



(855) 444-4286

Specifications

Module:	Sierra Wireless MC7455
Carrier Approvals:	Verizon, AT&T, T-Mobile, Sprint
Regulatory Approvals:	FCC, PTCRB, NCC, IC, GCF, CE
Frequency Bands:	4G LTE - B1, B2, B3, B4, B5, B7, B8, B12, B13, B20, B25, B26, B29, B30, B41 3G - WCDMA B1, B2, B3, B4, B5, B8
Peak Data Speeds LTE:	DL 300 Mbps/ UL 50 Mbps

Router:

VPN:	IPSec, OpenVPN, VPN Client, GRE
Protocol:	ICMP, TCP, UDP, Telnet, SSH, HTTP, HTTPS etc.
Management:	Local or remote web browser (IE v8 or above), CLI/Telnet command, Remote management, SSH configure
Interface Type:	5 x 10/100 Mbps port (RJ45) LED: "WLAN", "WAN", "LAN", "NET" 2 x SMA-K antenna interface SIM/UIM: 1.8V/3V Power: "PWR" 5V ~ 30V Reset: "RST"
Power Adapter:	Certificate: FCC, UL
Power Consumption:	Idle: <45mA@12VDC Data: <300mA@12VDC Average:150mA@12VDC
Physical:	Operating Temperature Storage: -40°C to 85°C Working: -30°C to 75°C Humidity: 95% Maximum (Non-condensing)
Dimensions:	Item (L x W x H): 6 x 4 x 1 Inch Packaging (L x W x H): 9.3 x 5.8 x 3 Inch Weight Item: 0.8 lbs. Packaging: 1.8 lbs. total weight including product
Certificates:	FCC, ISO, CE, RoHS
Package Content:	3500 - 5 Port Router CAT5 Ethernet Cable Power Adapter 2 x Cellular Antenna - Mag Mount

